



GWH-HW67AC84-EP- bullet camera

4.0MP IR Bullet Pro IP Camera

Features

- >1/3" 4.08 megapixel Progressive Scan CMOS
- >Support H.265/H.264/MJPEG codec
- >Max 25fps@4.0MP(2592×1520); Dual streams
- >Day/Night(ICR)&3D DNR&AWB&AGC
- >WDR up to 100dB
- >P2P Cloud Monitoring
- >2.8-12mm @F1.4 Vari-focus Lens or motorized lens 2.8-12mm
- >Max IR Distance:30m
- >IP66, Micro SD Slot, PoE
- >Built-in Web server
- >Junction box optional



| | |
|--------------------|---|
| Model | GWH-HW67AC84-P |
| Général | |
| Main Processor | High-performance Hisilicon DSP |
| Operating System | Embedded LINUX |
| Resource | Simultaneous remote monitoring, local recording and remote control |
| User Interface | WEB, CMS, NVR |
| Camera | |
| Image Sensor | 1/3" 4.08MP progressive scan CMOS |
| Effective Pixels | 2688(H)×1520(V) |
| Electronic Shutter | 1/5s to 1/50,000s |
| Mini. Illumination | Color:0.1Lux/F1.2 ; B/W:0.005Lux/F1.2 |
| Signal Noise Ratio | >50dB |
| Day/Night Mode | Auto, dual IR-Cut filter |
| Gain Control | Auto/Manual |
| White Balance | Auto/Manual |
| WDR Dynamic Range | 100dB |
| Lens | M14,2.8mm~12mm @F1.4 Vari-focus Lens |
| Max IR Distance | 30m, 4pcsΦ28mil LED |
| Video | |
| Video Compression | H.265/H.264/MJPEG Optional |
| Coding standard | H.265 Main Profile / H.264 Baseline/H.264 Main Profile/H.264 High Profile Optional |
| Video Bit Rate | Main Stream: 200Kbps~12Mbps Sub Stream: 100Kbps~6Mbps |
| Image Resolution | 4.0MP(2592x1520) / 3.0MP(2048x1520)/1080P(1920X1080)/ 720P(1280×720) / D1(704×576)/CIF(352x288) |
| frame Rate | Main Stream: 2592x1520(1~25fps) SUB Stream: 1280x720(1~25fps) |
| Video Format | PAL/NTSC |



GWH-HW67AC84-P- bullet camera

4.0MP IR Bullet Pro IP Camera

| | |
|----------------------------|--|
| Model | GWH-HW67AC84-EP |
| Network | |
| Ethernet | RJ-45 (10/100Base-T) |
| Network Protocol | IPv4/IPv6,HTTP HTTPS TCP/IP UDP UPnP ICMP IGMP SNMP RTSP RTP SMTP NTP DHCP DNS PPPOE DDNS FTP IP Filter QoS Bonjour802.1x P2P cloud |
| Compatibility | Linux/windows C/C++ SDK / ONVIF v2.42 / CGI API |
| Max User Access | 10 users |
| Smart phone | Iphone , Ipad ,Android, |
| Remote Operation | Monitor, Playback, System setting, File download, Log information, Maintenance & Upgrade |
| Auxiliary Interface | |
| Reset button | Yes |
| Memory Slot | TF Card Max 64GB |
| RS485 | Yes(half-duplex) |
| Alarm Input | 1ch NC/NO |
| Alarm Output | 1ch 120VAC 1A/24VDC 1A |
| Video Output | 1chBNC75 ohms |
| Environmental | |
| Power Supply | DC12V±10% |
| Power Consumption | <10W |
| Operating Environment | -40°C ~ +60°C, Humidity less than 95%(Non-condensing) |
| PoE | YesIEEE802.3af |
| Protection Level | IP66 |
| Dimensions(mm) | 286 x 79 x 86 |
| Weight(kg) | 0.98 Kg |

Dimensions (mm)

